


Terminals Series

KLS8-01109 Male and female full-insulating terminal Series

Maximum Electrical Rating: 75°C 300 Volts MAX.
Insulation Material: VINYL
Terminal Material: BRASS

VIII



Item No.	Section of lead	Nema tab mm	Dimension					COLOR
			W mm	B mm	D mm	d mm	L mm	
FD1.25-187(5)	0.5~1.5mm ² (22~16A. W. G.) I Max=10A	0.5*4.75	7.6	5.6	3.8	1.7	20.0	RED
FD1.25-187(8)		0.8*4.75	7.6	5.6	3.8	1.7	20.0	
FD1.25-250		0.8*6.35	9.4	7.4	3.8	1.7	21.5	
FD2-187(5)	1.5~2.5mm ² (16~14A. W. G.) I Max=15A	0.5*4.75	7.6	5.6	4.3	2.3	20.0	BLUE
FD2-187(8)		0.8*4.75	7.6	5.6	4.3	2.3	20.0	
FD2-250		0.8*6.35	9.4	7.4	4.3	2.3	21.5	
FD5.5-250	4~6mm ² (12~10A. W. G.) I Max=24A	0.8*6.35	9.4	7.4	5.7	3.4	25.5	YELLOW

ORDER INFORMATION

KLS8-01109 - FDFD1.25-187(5)

