

CdS Photoconductive cells

3mm CdS photosensitive resistor

Product Model: KLS6-3548

FEATURE:

- Epoxy encapsulated
- Quick Response
- Small Size
- High Sensitivity
- Reliable Performance
- Good Characteristic of Spectrum



TYPICAL APPLICATIONS:

- Auto Flash For Cameras
- photoelectric Control
- Optical Control Lamp
- Room Light Control
- Photomusical I.C.
- Industrial control
- Photoswitch
- Electronic Toys

DESCRIPTION:

CdS Photoconductive Cells is a resistor which made of semi-conductor material, and the conductance change with luminance variation. The CdS Photoconductive cells can be manufactured with different figures and illuminated area based on this characteristic. CdS Photoconductive cells is widely used in many industries, such as toys, lamps, camera, etc.

ELECTRO-OPTICAL CHARACTERISTICS :

Parameter		Characteristics	Unit
Light Resistance(at 10lux)		45-140	KΩ
Dark Resistance(at 0 lux/Min)		5.0	MΩ
Gamma Value(at 100-10lux)		0.8	γ_{10}^{100}
Power Dissipation(at 25°C)		50	MW
Max Voltage(at 25°C)		100	VDC
Spectral Response peak(at 25°C)		540	nm
Ambient Temperature Range		-30~+70	°C
Response time	Increase	30	ms
	Decrease	30	ms

- ※ Light resistance : Measured at 10lux(standard Light source)at a color temperature of 2856K. color temperature)and 2h pre-illumination at 400-600 lux priorto testing .
- ※ Dark resistance: measured 10 seconds after pulsed 10 lux.
- ※ Gamma Characteristic:between 10lux and 100lux and given by $T = \frac{\text{Log}(R_{10}/R_{100})}{\text{Log}(100/10)} = \text{Log}(R_{10}/R_{100})$
- ※ Pmax: Max.power dissipation at ambient temperature of 25°C.
- ※ Vmax:Max.voltage in darkness that may be applied to the cell continuously .



3mm CdS photosensitive resistor


Product Model: KLS6-3548




Component Information :

Component Name	ROSH	Notice
Resin Coating	YES	--
CdS	NO	Composition than 100 PPM
Electrode	YES	--
Ceramic Substrate	YES	--
Lead Terminal	YES	--

SCHEMATIC DRAWING :



OUTLINE:(Unit: mm)




CdS Photoconductive cells


3mm CdS photosensitive resistor

Product Model: KLS6-3548

■ SPECTRAL RESPONSE :



■ ILLUNINANCE Vs. PHOTO RESISTANCE



3mm CdS photosensitive resistor

Product Model: KLS6-3548



TEST CONDITIONS

Light Resistance Dark Resistance	Light resistance:A light source(2856k) At 10Lux Dark resistance:data @10sec,after cutting off 10Lux light r=Lg (R10/R100)	Workable
Tempure Change Testing	Hight tempture:: 70°C±5°C Time:30M Incideng light:dark placing Testing time:24hr Low tempture::-30°C±5°C Time:30min Incident light:above dark placing as a recycle,testing time:24hr	Workable
Constant Tempure Testing	Tempure:40±5°C Moisture :90-95% Incident light:dark placing Testing time:48hr	Workable
Lead High Tempure Testing	At the root of lead 90 degree curving,5mm above the root,loading 100g charge Welding tempture:: 260°C Heating time:Max.35,distance between welding and base:5mm	Workable

PACKING AND PRECAUTION:





Image -01



CdS Photoconductive cells

3mm CdS photosensitive resistor

Product Model: KLS6-3548




Image-03

IMAGE NO.	NAME	QUANTITY
Image-01	Bag	200Pcs /bag
Image-02	Box	10Bag/Box = 2000Pcs
Image-03	Carton	20000PCS = 10 Box = 100 Bag = 1 Carton

- This product is packed with the environmental protection material,200pcs per small package,2000pcs per big package.
- Avoid high temperature and humidity for storing.
- Soldering should be completed in the shortest possible time.
- It is recommended that the soldering should keep 4mm away from ceramic substrate.