

KLS ELECTRONIC CO., LTD.

Standard & General BLDC




5	KLS23-B2415M	Output Power: 0.2W~2W	Weight: 24g (Approx.)					
	Brushless DC Motor-Typical Application							
	Home Application: White Goods, Small Appliance, Micro Fanner							
	Medical Apparatus: Medical Pump, Blood Pressure Meter							
0	Industry Device: Instrument & meter, Electric Valve, Optoelectronic device, Office Automation,							
	Multimedia Entertainment device							
1	Business Equipment: Printer, Copier, Projector, Scanner, Cash Register							
the second secon	Personal Care: Hair Dryer, Electric Shaver, Vibrator							


	Voltage(V)		No Load		Rated Load			Starting		
Model	Operating Range Rated	Pated	Speed	Current	Torque	Speed	Current	Output	Torque	Current
		(rpm)	(A)	(mNm)	(rpm)	(A)	P. (W)	(mNm)	(A)	
B2415M-S01	8-26	12	6840	0.051	1.962	4350	0.183	0.893	5.35	0.41

Characteristic: CW & CCW, Signal function available, Locked rotor protection, Stepless speed regulation, Low noise, Low EMI, Long life 10000-30000hrs

Notice: Data in this typical specification sheet are for other certain customer. Voltage, rated torque, speed, current, power and shaft extension feature & dimension can be changed to meet customer specific requirement.

Outline Drawing:






Usable machine screw length 1.5mm max. from motor mounting surface **Performance Curve:**



12V



Unit: Millimeter