


	KLS23-B3640G	Output Power: 1W~16W	Weight: 295g (Approx.)
	Brushless DC Gear Motor-Typical Application Home Application: Electric door, Electric Window, Electric Curtain, Electric Awning Industry Facility: Transmission Equipment, Gear System, Actuator Electronic Equipment: Electric Valve, Small Switcher, Lighting Adjustor, Small Percussion Drill Business Equipment: Electric Gate, Banking Facility, ATM, Vending Machine Personal Care: Massager		

Model	Voltage(V)		No Load		Rated Load			Starting		
	Operating Range	Rated	Speed (rpm)	Current (A)	Torque (Nm)	Speed (rpm)	Current (A)	Output P. (W)	Torque (Nm)	Current (A)
B3640G-S01 (Gear Ratio 27)	8-26	24	147	0.19	0.597	116	0.70	7.28	2.66	2.67
B3640G-S02 (Gear Ratio 27)	8-26	24	150	0.24	1.27	120	1.19	13.0	2.83	2.86

Characteristic: CW & CCW, Signal function available, Locked rotor protection, Stepless speed regulation, Low noise, Low EMI, Long life 10000-30000hrs

Notice: Data in this typical specification sheet are for other certain customer. Voltage, rated torque, speed, current, power, gear box ratio & dimension, shaft extension feature & dimension can be changed to meet customer specific requirement.

Outline Drawing:



Unit: Millimeter

BLDC Motor Performance Curve:

B3640G-S01(Bare Motor)

24V

