

INDUCTORS

SMD Molded Wound Chip Inductor CM453232 Series

Part Number	Inductance μH	Std. Tolerance	Q min.	Test Freq. MHz	SRF min. MHz	RDC max ohm	IDC max mA
CM453232-R10 M	0.1	±20 %	35	25.2	300	0.18	800
CM453232-R12 M	0.12	±20 %	35	25.2	280	0.2	770
CM453232-R15 M	0.15	±20 %	35	25.2	250	0.22	730
CM453232-R18 M	0.18	±20 %	35	25.2	220	0.24	700
CM453232-R22 M	0.22	±20 %	40	25.2	200	0.25	665
CM453232-R27 M	0.27	±20 %	40	25.2	180	0.26	635
CM453232-R33 M	0.33	±20 %	40	25.2	165	0.28	605
CM453232-R39 M	0.39	±20 %	40	25.2	150	0.3	575
CM453232-R47 M	0.47	±20 %	40	25.2	145	0.32	545
CM453232-R56 M	0.56	±20 %	40	25.2	140	0.36	520
CM453232-R68 M	0.68	±20 %	40	25.2	135	0.4	500
CM453232-R82 M	0.82	±20 %	40	25.2	130	0.45	475
CM453232-1R0 K	1	±10 %	50	7.96	100	0.5	450
CM453232-1R2 K	1.2	±10 %	50	7.96	80	0.55	430
CM453232-1R5 K	1.5	±10 %	50	7.96	70	0.6	410
CM453232-1R8 K	1.8	±10 %	50	7.96	60	0.65	390
CM453232-2R2 K	2.2	±10 %	50	7.96	55	0.7	380
CM453232-2R7 K	2.7	±10 %	50	7.96	50	0.75	370
CM453232-3R3 K	3.3	±10 %	50	7.96	45	0.8	355
CM453232-3R9 K	3.9	±10 %	50	7.96	40	0.9	330
CM453232-4R7 K	4.7	±10 %	50	7.96	35	1	315
CM453232-5R6 K	5.6	±10 %	50	7.96	33	1.1	300
CM453232-6R8 K	6.8	±10 %	50	7.96	27	1.2	285
CM453232-8R2 K	8.2	±10 %	50	7.96	25	1.4	270
CM453232-100 K	10	±10 %	50	2.52	20	1.6	250
CM453232-120 K	12	±10 %	50	2.52	18	2	225
CM453232-150 K	15	±10 %	50	2.52	17	2.5	200
CM453232-180 K	18	±10 %	50	2.52	15	2.8	190
CM453232-220 K	22	±10 %	50	2.52	13	3.2	180
CM453232-270 K	27	±10 %	50	2.52	12	3.6	170
CM453232-330 K	33	±10 %	50	2.52	11	4	160
CM453232-390 K	39	±10 %	50	2.52	10	4.5	150
CM453232-470 K	47	±10 %	50	2.52	10	5	140
CM453232-560 K	56	±10 %	50	2.52	9	5.5	135
CM453232-680 K	68	±10 %	50	2.52	9	6	130
CM453232-820 K	82	±10 %	50	2.52	8	7	120
CM453232-101 K	100	±10 %	40	2.52	8	8	110
CM453232-121 K	120	±10 %	40	0.796	6	8	110
CM453232-151 K	150	±10 %	40	0.796	5	9	105
CM453232-181 K	180	±10 %	40	0.796	5	9.5	102
CM453232-221 K	220	±10 %	40	0.796	4	10	100
CM453232-271 K	270	±10 %	40	0.796	4	12	92
CM453232-331 K	330	±10 %	40	0.796	3.5	14	85
CM453232-391 K	390	±10 %	40	0.796	3	18	80
CM453232-471 K	470	±10 %	40	0.796	3	26	62
CM453232-561 K	560	±10 %	30	0.796	3	30	50
CM453232-681 K	680	±10 %	30	0.796	3	30	50
CM453232-821 K	820	±10 %	30	0.796	2.5	35	30
CM453232-102 K	1000	±10 %	30	0.252	2.5	40	30