

Rotary switches* Coding switches





L-KLS7-RS30807 10*10 8 Postion Rotary Dip Switches

Materials:



COVER: Engineering Plastics, Black or Blue
BASE: Engineering Plastics, Black or Blue
KEY: Engineering Plastics, White or Orange
TERMINAL: Alloy Copper, Plating Gold or Tin

Electrical:


Switching Rating: 25mA 24V DC
Contact Resistance: 50mΩ Max.
Insulation Resistance: 1000MΩ MIM
Dielectric Strength: AC 500V 1Minute
Operation Force: 500gf-cm Max.
Operating Temperature: -20~+70°C
Electrical Life: 20,000 Cycles



CIRCUIT DIAGRAM




CONSTRUCTION



CODE:

R	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
C	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
2			•	•	•	•	•	•	•	•	•	•	•	•	•	•
4				•	•	•	•	•	•	•	•	•	•	•	•	•
8					•	•	•	•	•	•	•	•	•	•	•	•



ITEM	DES	MATERIALS	TREATMENT
1	COVER	ENGINEERING PLASTICS	BLACK
2	BASE	ENGINEERING PLASTICS	BLACK
3	KEY	ENGINEERING PLASTICS	WHITE
4	TERMINAL	ALLOY COPPER	GOLD

ORDER INFORMATION

L-KLS7-RS30807

Part Number

RS: ROTARY DIP SWITCH

Serial number