



**Electrical :**

Rated voltage: 250V

Rated current: 10A

Contact resistance: 20mΩ

Insulation resistance: 5000MΩ/1000V

Withstanding Voltage: AC1500V/1Min

Wire range: 22-14AWG 1.5mm<sup>2</sup>

**Material**

Housing: Polyamide Glass Filled UL94V-0

Contact: Brass(CuZn),Nickel Plated

Screws: M2.6 steel Nickel plated

Wire guard: Beryllium Copper, Tin Plated

**Mechanical**

Temp. Range: -30° C ~ +105° C

Torque: 0.4Nm (3.5lb.in)

Strip length: 6mm

**Order Information**

L-KLS2-331KB-5.00-XXP- 3 S

Screw: Slot Screw

Color: Black

Number of Pole: 02 ~ 24P

GENERAL TOLERANCE	ANGLE TOLERANCE	PROJECTION	Description:
X. ±0.60	X. ±5°	UNITS	Terminal block 5.0mm Pitch, Black,Without Cover;2 - 24P
.X ±0.38	.X ±3°	SHEET SIZE	
.XX ±0.25	.XX ±2°	KLS P/N:	

Draw by: Date	
Check by:: Date	
SCALE	SHEET OF

KLS ELECTRONIC CO., LTD.